



## The real accessories for CAD / CAM

Article-No.	Execution	Use	Measurements
4200 white	heatfix quality, 62 g/m <sup>2</sup>	for ironing drawings of master on the fabrics	Length: 250 m, 300 m Width: 155,165,182,205cm
4050 recycling			Length: 250 m Width: 155,165,182 cm
5000 white			
5002 recycling			
5013 recycling	normal quality, 55 g/m <sup>2</sup>	For fixing drawings of master on the fabrics	Length: 270 m Width: 155,165,185,205cm
5003 white			Length: 270 m Width: 76,81,91,101,155,165,185,205 cm

### Plotter paper

made of extremely strong special paper. To be used for all plotters.

Article-No.	Execution	Use	Measurements
5004 white	heatfix quality, width: 76-101 cm =12 rolls/box width: from 142 cm up =6 rolls/box	for making copies 1:1 by blue print machines and ironing on the fabrics	Length: 50, 100 m Width: 76,81,91,101,142, 152,162 cm
5005 white	normal quality width: 76-101 cm =12 rolls/box width: from 142 cm up =6 rolls/box	for making copies 1:1 by blue print machines and immediate cutting of the fabrics	Length: 50, 100 m Width: 76,81,91,101,142,152, 162 cm

### Blue print paper

Article-No.	Execution	Use	Measurements
4041 white	heatfix quality with spot and cross markings, 62 g/m <sup>2</sup>	for drawing master copies by hand and immediate ironing on the fabrics	Length: 300 m Width: 155,162,182, 202 cm
4042 recycling			Length: 280 m Width: 76,81,91,101,152,162,182, 202 cm
4043 recycling	normal quality with spot and cross markings, 55 g/m <sup>2</sup>		Length: 300 m Width: 155,165,182, 205 cm

### Cutting paper

made of extremely strong special paper

Article-No.	Execution	Use	Measurements
5112	microperforated 60 g/m <sup>2</sup>	for fixing of the layers by vacuum sucking on the	Length: 210 m Width: 92, 122, 152, 162, 183, 203 cm
5117	microperforated 80 g/m <sup>2</sup>		
5123	macroperforated 60 g/m <sup>2</sup>		Length: 280 m Breite: 76,81,91, 120, 182, 202, 220 cm
5120	macroperforated 80 g/m <sup>2</sup>		

### Underlay paper

fully perforated kraft paper.

Article-No.	Execution	Use	Measurements
5119	even 60 g/m <sup>2</sup>	for fixing of the layers by vacuum sucking on the table	Length: 210 m Width: 76,81,152,162,185,202 cm
51191	even 80 g/m <sup>2</sup>		
5150	even 70 g/m <sup>2</sup>		Length: 200 m, Width: 160,172,185,202 cm

### Unterlay paper

Article-No.	Strength (my)	Fitted	Width of roll (mm)	Length of roll (m)
5061	15-30	with antistatic effect	1800-2450	700-1000

### Low pressure film

air-proof film with high density