



Jumru


Jumru[®]



Table of Contents

Yarn Brakes/Detector..... 2

Yarn Brakes/Detector



Disk brake

Model: 3159

Disk brake, holed and slotted shaft, high gloss nickel-plated, forstop motion 3106.



Disk brake

Model: 3690

Disk brake for circular knitting machines, vertical shaft holed and slotted, with 2 metal tension disks.



Disk brake

Model: 3160/1


Disk brake, holed and slotted shaft, high gloss nickel-plated, 0.4 mm spring wire.



Friction type tension

Model: 4123

Friction type tension for all yarns, particularly for fine and smooth threads, adjustable tension effect, to be used horizontally or vertically.



Lower end detector

Model: 3781


Lower end detector, as 3780, but two ends; feelers stopping individually to be set on different yarn tensions.



Lower end detector

Model: 3780


Lower end detector, as 3716/2, but closed guide stirrup, in order to eliminate entanglements in case of man made fibres, eyelets of hard ceramic.



Mini needle detector

Model: 3754

Mini needle detector, 24 Volt working circuit, detects broken needles or loops, for circular looms.



Needle detector

Model: 3743

Needle detector, 24 Volt, with pilot lamp, without bracket, for circular looms Mayer & Cie.



Needle detector

Model: 4133

Needle detector for circular and flat knitting machines and stocking looms for control of knitwear and needles.

Technical data:

Working voltage: 24 V alternating current.

Safety stop motion

Model: 3106/1



Safety stop motion. 24 Volt, with alarm lamp, detecting broken end, empty supply, and knots.



Stop motion

Model: 3744

Stop motion, with light indication, 12 Volt, switch contact on yam break or too low tension and on excessive yam tension. yam tension adjustable, with thread guides of hard ceramic.

