



Jumru

Jumru®



Table of Contents

Bagging Machines 2

Bagging Machines



Packing Machine HP630KST

Model: 0.621.058

Technical data:

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 570 x 2030 mm

Weight approx.: 48 kg



Packing Machine HP630KST-P

Model: 0.621.034

Technical data:

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 570 x 2030 mm Weight approx.: 48 kg.



Packing Machine HP630KW

Model: 0.621.026

Technical data:

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 570 x 560 mm

Weight approx.: 40 kg

**Packing Machine KST-BS**

Model: 0.621.061

Technical data:

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 670 x 2230 mm

Weight approx.: 91 kg

**Packing Machine KST-BS**

Model: 0.621.059

Technical data:

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 670 x 2230 mm

Weight approx.: 91 kg

**Packing Machine KST-BS-P**

Model: 0.621.075

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 670 x 2230 mm

Weight approx.: 91 kg



Packing Machine KST-BS-P

Model: 0.621.073

Technical data:

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 670 x 2230 mm

Weight approx.: 91 kg



Packing Machine KW-P

Model: 0621.031

Technical data:

Film width max.: 600 mm

Fil thickness 0,02 mm

Mains connection: 230 V/50 Hz.

Dimenions (w x d x h): 810 x 570 x 560 mm

Weight approx.: 40 kg.

