



*Jumru*

**Jumru**<sup>®</sup>



---

## Table of Contents

Spead Measuring..... 2

## Speed Measuring

Articulating arm incl. mounting kit for Handstroboscope

Model: 4022/6

Belt bag with clip for Handstroboscope

Model: 4022/3

Li / Ion Battery Smart Pack for Handstroboscope

Model: 4022/5



Precision Tachometer

Model: 3991

Range from:

40 to 50,000 t.p.m. and from 4 to 5,000 m.p.m. to be set into

the following steps: 40 to 500 t.p.m. and from 4 to 50 m.p.m. 400 to 5,000

t.p.m. and from 40 to 500 m.p.m. 4,000 to 50,000 t.p.m. and from 400 to 5,000 m.p.m. In handy box 85 x 155 x 45 mm, with 1 rubber point, rubber bush, rubber funnel, wheel disk, and extension. Weight of approx. 580 g.

Precision Tachometer for all rotary or linear speed measurements, independent of sense of rotation. Locking button for showing the result, patented reverse gear, indifferent to change of temperature, and to magnetic fields. Deviation  $\pm 0,5 \%$ .

Replacement Xenon Lamp for Handstroboscope

Model: 4022/1

---

Spare parts Electronics for Handstroboscope

Model: 4022/7

Tripod, 3-way adjustable for Handstroboscope

Model: 4022/4

Worldwide charger set (100-230V) for Handstroboscope

Model: 4022/2

