




Ironing accessories from 



6110 - 6110/1

**6110** Heatseal - Iron for fast and uniform ironing of heatseal-paper, with set-up system for lateral tilting of the ironing plate. Shoe size 750 x 150 mm, connected load 220 Volt, capacity 2,000 Watt, weight approx. 4.5 kg. Drawn ironing-shoe made of hard aluminium alloy. Uniform and fast heating of the ironing-shoe by two tube radiators with high connected load. Precise heat regulation from 60° to 230° C by thermostat, indicated by signal lamp. Light weight, thus easy handling. Optimum shoe size for ironing of wide layers. Connection cable and piece for protection of cable, made of silicone rubber. Long insulating handle, easily accessible from all sides. Quick and easy exchange of thermostat and tube radiators.

**6110/1** Heatseal-Iron as 6110, but capacity 3,000 Watt.

**6110/2** Thermostat for heatseal iron No. 6110/1

**6110/3** Heating resistor 1.000 W for heatseal iron

**6110/4** Thermostat for heatseal iron No. 6110



6156

**6156** Steam Iron with heat refusing cork handle, temperature can be regulated by thermostat 0 - 235° C, iron sole 10 x 20 cm, weight 1,4 kg, alternating current 220/240 Volt, 50 cycles, capacity 800 Watt.



6103



6106

**6103** Pad for irons, red, silicone coated, size 230 x 140 mm.

**6106** Cleaning stick for fast and safe cleaning of iron soles or other hot faces. Put the stick onto the hot face, have effected it for some seconds, and then rub off with a dry, rough rag. In case of resistant stains, repeat the operation. Available per 10 sticks.



6107

**6107** Cleaning Paste for fast and safe cleaning of iron soles or other metal faces of presses. Put the paste onto the hot place with a soft rag in circular movements, and then rub off with a clean rag.

**6114** Cleaning Pads, of fine steel wool, for removing residues from iron soles or plates.



6114



3499

**3499** Ironing gloves, with thick foam rubber and PVC filler, oval shape.



**6092** Temperature measuring strap, for simple but exact checking of fixing temperature between upper fabric and filler during the fixing operation. Available in boxes of 40 straps; measuring range 104° to 143° C.

**6093** Temperature measuring strap as 6092, but measuring range 143° to 182° C.

**6094** Temperature measuring strap as 6092, but measuring range 182° to 224° C.



6092-6094

## Correct equipment of ironing tables from

**6096** Precision Spray Gun for wetting garments and cut cloths during ironing. Corrosion -proof, fine and uniform jet, low water consumption, on/off switching without dropping, handy shape, connection to all water pipes, nozzle hole 0.5 mm, without tube nipple.

**6157** Lining Spraying Device for lining place, for ironing fabrics which are sensitive for brightness, consisting of gun, pressure valve with manometer, water tank inclusive tubes. extra-stand with returning spring for gun.

**6157/1** Lining Spraying Gun for lining place 6157.

**9084/1** Silicon - deviding material with high intensity, type Baysilon in spraying bottles of 300 g.

**9099** JOMRO Slide - Spray, in spraying bottles of abt. 520 g contents. A slide spray with outstanding features: it smoothes without greasing, it is rust and dirt rejecting, it is clear as water, it does not effect colours, it does not leave spots or stains. Example for application: for smoothing sewing machines or cutting tables, or any other table, for smoothing band knives, percussion knives, circular knives, for smoothing iron soles, for smoothing slide bars and conveyors, for smoothing sewing machine needles, for other purposes.

**4205** Streckfix- (bur)-material, perforated, without connection piece, prevents the lateral rolling-off of flat knitted goods at steam tables, steam dummies or fixing plants.

**4208** Bristle case for ironing of velvet and filmy fabrics.

**4210** Nylon cover for ironing tables as upper cover, brown, 150 cm wide.

**4211** Polyester wire grate, 150 cm wide, as intermediate ply directly under the upper cover, prevents displacing of the pads.

**4212** Polyester felt as pad, 6 mm thick, 140 cm wide

**4213** Silicone foam, anthracite, solid, as padding, 6 mm thick, 130 cm wide.



6096



6157/1

**BRISAY**



6157




9084/1



9099

**Cover for ironing tables for all brands**



4205




4208



4210



6091/1-12



Drawing for iron soles



9271



9243

Please note our new ironing set

4237/1-3



4234/4235

**T**eflon Iron Soles, with heavy frame of aluminium, reinforced sole, with retaining spring. Avoids sheen and burning, particularly for delicate fabrics. Of course, we are supplying as well iron soles for all other brands of iron. In case of need please send us a pasteboard pattern, indicating exactly the required measurements. Please note our example below.

Article-No.	Suitable for:	Article-No.	Suitable for:
6091/1	Aqua-Steam	6091/5	Cissel
6091/2	Veit HD 2000	6091/9	Hoffmam EDM 2
6091/4	Bishomatic	6091/12	Iron Master

**Table 39**

**9271** Silicon - Cleaner Rollax - Powder in tins of 250 g, for cleaning of thermoplastic rests of adhesives substances. Rollax contents highly viscous silicon, which guarantees a complete remove of rests of adhesives substances.

**9243** Matting Brush of horsehair and brass wire, 350 x 84 x 28 x 20 mm, for gloss removing on all cloths.

**4209** Ironing set with important help for right ironing. The ironing set consists of the following articles:

- **Aerofit** for preventing stripes on the material to be ironed. It can be cut into corresponding sizes and is to be put between iron sole and frame sole, thus ensuring that the steam is better spreaded out. Available in meters, 101 cm wide.

- **Prefit fine**, to be applied as underlay material when ironing pocket flaps and lapels, thus preventing marks on the material. Available in meters, 105 cm wide.

- **Needle fabrics** will be put with the needles onto the velvet and velours to be ironed, thus preventing marks. Available in meters, 150 cm wide.

- **Needle woven fabrics** as well as needle fabrics against gloss in those cases where the needles leave marks on the material. Available in meters, 150 cm wide.

- **Anti-gloss-spray-set** to be sprayed onto the material to be ironed and afterwards treated by dry steam. The set consists of 2 sprays per 250 ml and 1 spraying bottle of 100 ml.

**4237** Delimer to dissolve limestone, rust and scale for water systems, without acid, sediments will be removed effectively, no aggressive vapours

**4237/1** Bottle of 1 litre

**4237/2** Can of 5 litres

**4237/3** Can of 25 litres

**4234** Binding agent "Lapidon". The chalk contained in the water may deposit in the boiler and on the heating elements which may cause breakdowns. Lapidon is recommended if the water hardness exceeds 5 ° dH (German hardness). The chalk will be removed from the boiler during blow-down.

**4234** Bottle per 125 ml

**4235** Bottle per 500 ml